

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE

	MATERIAL NAME	RUSTPROOF-06	
	USES	: LOW VISCOS RUST PREVENTIVE OIL	
	MANUFACTURER	: Emulsichem Lubricants Pvt Ltd T-120, MIDC, Bhosari, Pune-411026, Maharashtra, India	\leq
	Emergency Contact Number	: Tel-+91 20-27120266 / 77, +91 9822064232 E-mail:- <u>abhijeetbhosale@emulsichem.com</u>	
2.	COMPOSITION/ INFORMATION ON INGREDIENTS:		
3.	Preparation Description HAZARDS IDENTIFICATION:	: Blended with anti-corrosion agents and Highly refined Low viscose mineral base oil.	
5.	Health Hazards	: It is not expected to be a health hazard When used under Normal conditions and Controlled working parameters. Prolonged skin contact may cause some Disorder like acne and rashes. Impurities In used oil can be avoided by Regular filtration of chips.	
	Safety Hazards	: Not flammable, but will burn	
	Environmental Hazards	: Not classified as dangerous for the Environment	
4.	FIRST AID MEASURES: General Information	: No treatment is necessary. But may obtain Medical Advice.	
	Skin Contact	: For repeated skin contact flush with water And wash Hands with soap. Remove the Contaminated clothing. With persistent Irritation, please seek medical attention.	
	Eye Contact	: Flush with generous amount of water. If irritation Persists, seek medical advice.	$\mathbf{<}$
	Ingestion	: No treatment is necessary unless large Quantities are taken. In such cases please Seek medical attention.	



Notes to Physician

Special Information

: Please treat as per the symptoms with the Product Information

5. FIRE FIGHTING MEASURES

Flash Point Auto Ignition temperature Flammable Limits in air % by vol.: NA Extinguishing Media : NA : NA

INA

: Chemical foam type, Dry powder, Carbon di Oxide Sand may be used for Small fires. : N/A

6. ACCIDENTAL RELEASE MEASURES

Please avoid contact with spilled material. For further information on protective

Equipment see chapter 8 and for disposal of spilled material see chapter 13 of the

MSDS. If possible eliminate all ignition points, sources.

Protective Measures: Avoid contact and prevent from spreading
Or entering Drains or water.Cleaning Measures: Soak up with absorbent material like cloth,
Sand or other Suitable material.
Dispose as per guidelines.

7. HANDLING ANS STORAGE

Handling	: While handling drums, use safety shoes and Other Protective gear and handling	
	Equipment's	
Storage	: Store in cool properly ventilated area.	
	Storage Temperatures: 5-45 ° c	

8. EXPOSURE CONTROL/ PERSONAL PROTECTION

Respiratory	: Under normal conditions, no protection is Required. (If required provide air exhaust in Case mist is formed.)
Еуе	: Wear safety glasses if coolant splashes are Likely to Occur.
Hand	: If required hand gloves may be used. Personal hygiene is a must in case of using Hand gloves.



9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance Odour Solubility Density @ 27° C gm/ml Viscosity in C.st @ 40°c % volatiles by volume @ 21°c Boiling Point Melting Point Flash Point Vapour Density (Air) Vapour pressure (mm Hg) Evaporation Rate
- Clear light brown
 Slight odour
 Water insoluble
 0.83 ± 0.02
 6 ± 2
 NA
 Above 360°c
 NA
 110 ± 5°C
 No data available
 No data available
 No evaporation at room temperature

10. STABILITY AND REACTIVITY

Stability Hazardous decomposition

Hazardous Polymerization Conditions to avoid

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity Acute Dermal toxicity Skin irritation Eye irritation Respiratory irritation

Carcinogenicity

- : Stable at room temperature
- : No hazardous products are formed during Products

Normal storage and use

: No polymerization occurs

- : Direct sunlight and extreme pressure
- : Expected to be of low toxicity
- : Expected to be of low toxicity
- : Expected to be slightly irritating
- : Expected to be slightly irritating
- : In case of mist, inhalation may cause Irritation.
- : Components are not known to be Associated with Carcinogenic effects at The usage doses.

12. ECOLOGICAL INFORMATION

Environmental toxicity

: May cause physical fouling of aquatic Organisms if left Untreated. Not readily Biodegradable.





13. DISPOSAL CONSIDERATIONS

The product can be treated in the ETP before disposing. It the responsibility of the Waste generator to determine the toxicity and physical properties of the material Generated after treatment with proper classification and disposal compliance.

14. TRANSPORT INFORMATION Domestic (Land) : This is not classified as dangerous **15. REGULATORY INFORMATION** The Factories Act, 1948, The Second Schedule : Permissible levels of certain Substances in work environment **16. OTHER INFORMATION** MSDS effective date : 01.01.2017

DISCLAIMER

This information is furnished without warranty, expressed or implied, except that it is Accurate To the best knowledge of Emulsichem Lubricants Pvt Ltd. The data on this Sheet are related Only on the specific material designated herein. Emulsichem Lubricants assumes no legal Responsibility for use or reliance upon these data and the damages to life, property incurred Thereafter.